



### Regd. Off:

M/s. GLOBE TECH, 51, Old Dhamu Nagar,  
Puliyakulam, Coimbatore, Tamil Nadu,  
INDIA - 641 045

### Warehouse:

M/s. GLOBE TECH, Velayutham Palayam PO,  
Avinashi, Tamil Nadu,  
INDIA - 641 654



### Contact :

0422 - 4392333; 444  
customer@triumphrealtors.com



- GYPSUM BOARD
- PVC GYPSUM CEILING TILES
- T-GRID SYSTEM

## GYPSUM BOARD



Regular Gypsum Board is an ideal choice for interior walls, partitions and ceilings, which require no special protection from fire or moisture.

### Product Specification

| Thickness | Metric Size (mm) | Imperial Size (mm) | Weight (approx.) Kg./sheet |
|-----------|------------------|--------------------|----------------------------|
| 12.5 mm   | 1200 x 1800      | 1220 x 1830        | 17                         |

| Identification                              | Manufacturing Standards | Thermal Conductivity        |
|---------------------------------------------|-------------------------|-----------------------------|
| Grey face paper<br>Brown reverse side paper | IS 2095 – Part I, 2011  | 10.16 (W/m <sup>2</sup> K ) |

Gypsum Board consists of a non-combustible core, gypsum in particular and extra tough paper on both sides of boards. This special extra tough paper makes gypsum board strong and long lasting.

## PVC GYPSUM CEILING TILES



| Specification (mm) | Quantity (piece/box) | Thickness (mm) |
|--------------------|----------------------|----------------|
| 595*595            | 10pcs                | 7.0            |

### Characteristics

Advanced decorative materials featuring decoration, sound absorption, fire prevention, flame retardant, heat insulation, heat preservation, energy - saving insulation, etc.

### Application

Widely used in hotels, restaurants, shopping malls, theaters, ballrooms, stations, auditoriums, offices, living rooms, office buildings, precision instruments, interior decoration of factories or houses.

## T-GRID SYSTEM



| Title                  | Specification (mm) | Packing   |
|------------------------|--------------------|-----------|
| T Grid Main Tee        | 32*24*0.3*3600 mm  | 25pcs/ctn |
| T Grid Long Cross Tee  | 26*24*0.3*1200 mm  | 75pcs/ctn |
| T Grid Short Cross Tee | 26*24*0.3*600 mm   | 75pcs/ctn |
| Wall Angle             | 22*22*0.3*3000 mm  | 50pcs/ctn |
|                        | 22*22*0.3*3600 mm  | 50pcs/ctn |



### Features

- Maximum load carrying/m2 : 7.10 kg/m2
- Main runner loading meet to 11.67 kg/m
- Override end design resists twisting in cross tee
- Colour : Polished white color is standard.
- Material : Double web, hot-dipped galvanized steel in body.
- Installation : Must be installed in accordance with ASTM C636